



L142901930

LED E14 Tube T29x118mm 230V 1050Lm
10W 3000K 930 360° AC/DC Opaal
Dimbaar

Huishoudelijk, Tubular Premium



General		Energy		
Eprel registration no	831263	Operating voltage	230 V	
Socket	E14	Volt	220..240 V	
Bulb shape	T29	Frequency	50..60 Hz	
Width	29.00 mm	Watt	10 W	
Depth	29.00 mm	Current type	AC/DC	
Height	118.00 mm	Power factor	0.9	
Finish	Opal	Energy efficiency class	F	
Colour	White	Energy consumption	10 W	
Body material	Polycarbonat	Lamp efficacy	105.00	
Lifespan	25000 hours	LED		
Switches	50000	Filament LED	No	
Beam angle	360 °	LED type	SMD	
Dimmable	Yes	Dimm type	Trailing and leading edge	
Degree of protection	IP20	Number of leds / sticks	72	
Net weight	0.058 kg	Colour consistency SDCM	SDCM6	
Warranty	3 years	Dim to warm	No	
Light		Adjustable beam angle	No	
Kelvin	3000 K	Ordering details		
Colour temp nr	930	L142901930	Quantity pc(s)	EAN
Stable lumen	1050 lm	Single package	1	8718739063846
Color Rendering Index (CRI)	90	Inner carton	10	18718739063843
		Outer carton	100	28718739063840

