



L147239930

LED E14 Kogel G45x80mm 12-60V 250Lm
3W 3000K 830 160° DC Opaal Niet-Dimbaar

Marine & Industrie, General VR 12-60V Premium



| General | | Energy | | |
|-----------------------------|--------------|-------------------------|----------------|----------------|
| Eprel registration no | 831301 | Volt | 12..60 V | |
| Socket | E14 | Frequency | 50 Hz | |
| Bulb shape | G45 | Watt | 3 W | |
| Width | 45.00 mm | Current type | DC | |
| Depth | 45.00 mm | Power factor | 1 | |
| Height | 80.00 mm | Energy efficiency class | G | |
| Finish | Opal | Energy consumption | 3 W | |
| Colour | White | Lamp efficacy | 83.33 | |
| Colour housing | White | LED | | |
| Body material | Polycarbonat | Filament LED | No | |
| Lifespan | 25000 hours | LED type | SMD | |
| Switches | 50000 | Dimm type | Non-Dim | |
| Beam angle | 160 ° | Number of leds / sticks | 5 | |
| Dimmable | No | Colour consistency SDCM | SDCM5 | |
| Degree of protection | IP20 | Dim to warm | No | |
| Net weight | 0.015 kg | Adjustable beam angle | No | |
| Warranty | 3 years | Ordering details | | |
| Light | | L147239930 | Quantity pc(s) | EAN |
| Kelvin | 3000 K | Single package | 1 | 8718739055490 |
| Colour temp nr | 830 | Inner carton | 10 | 18718739055497 |
| Stable lumen | 250 lm | Outer carton | 100 | 28718739055494 |
| Color Rendering Index (CRI) | 82 | | | |

