



## L151801830

LED Ba15d Tube T18x80mm 230V 660Lm  
6W 3000K 830 360° AC/DC Opaal Dimbaar

### Marine & Industrie, Tubular Compact Premium



General		Energy		
Eprel registration no	831334	Operating voltage	230 V	
Socket	Ba15d	Volt	220..240 V	
Bulb shape	T18	Frequency	50..60 Hz	
Width	18.00 mm	Watt	6 W	
Depth	18.00 mm	Current type	AC/DC	
Height	80.00 mm	Power factor	0.9	
Finish	Opal	Energy efficiency class	E	
Colour	Colourless	Energy consumption	6 W	
Body material	Polycarbonat	Lamp efficacy	110.00	
Lifespan	25000 hours	<b>LED</b>		
Switches	50000	Filament LED	No	
Beam angle	360 °	LED type	SMD	
Dimmable	Yes	Dimm type	Trailing and leading edge	
Degree of protection	IP20	Number of leds / sticks	70	
Net weight	0.025 kg	Colour consistency SDCM	SDCM6	
Warranty	3 years	Dim to warm	No	
<b>Light</b>		Adjustable beam angle	No	
Kelvin	3000 K	<b>Ordering details</b>		
Colour temp nr	830	L151801830	Quantity pc(s)	EAN
Stable lumen	660 lm	Single package	1	8718739063907
Color Rendering Index (CRI)	80	Inner carton	10	18718739063904
		Outer carton	100	28718739063901

