



L152901930

LED Ba15d Tube T29x113mm 230V 1050Lm
10W 3000K 930 360° AC/DC Opaal
Dimbaar

Huishoudelijk, Tubular Premium



| General | | Energy | | |
|-----------------------------|--------------|-------------------------|---------------------------|----------------|
| Eprel registration no | 831339 | Operating voltage | 230 V | |
| Socket | Ba15d | Volt | 220..240 V | |
| Bulb shape | T29 | Frequency | 50..60 Hz | |
| Width | 29.00 mm | Watt | 10 W | |
| Depth | 29.00 mm | Current type | AC/DC | |
| Height | 113.00 mm | Power factor | 0.9 | |
| Finish | Opal | Energy efficiency class | F | |
| Colour | White | Energy consumption | 10 W | |
| Body material | Polycarbonat | Lamp efficacy | 105.00 | |
| Lifespan | 25000 hours | LED | | |
| Switches | 50000 | Filament LED | No | |
| Beam angle | 360 ° | LED type | SMD | |
| Dimmable | Yes | Dimm type | Trailing and leading edge | |
| Degree of protection | IP20 | Number of leds / sticks | 72 | |
| Net weight | 0.059 kg | Colour consistency SDCM | SDCM6 | |
| Warranty | 3 years | Dim to warm | No | |
| Light | | Adjustable beam angle | No | |
| Kelvin | 3000 K | Ordering details | | |
| Colour temp nr | 930 | L152901930 | Quantity pc(s) | EAN |
| Stable lumen | 1050 lm | Single package | 1 | 8718739063853 |
| Color Rendering Index (CRI) | 90 | Inner carton | 10 | 18718739063850 |
| | | Outer carton | 100 | 28718739063857 |

