



L480103665

LED PLL 2G11 4 pin Glas T44x410mm 230V
2300Lm 18W (PLL36W) 6500K 865 AC
Opaal Niet-Dimbaar

Marine & Industrie, PLL 2G11 4pin



General		Energy		
Eprel registration no	2039271	Operating voltage	230 V	
Socket	2G11	Volt	220..240 V	
Bulb shape	T44	Frequency	50..60 Hz	
Width	44.00 mm	Watt	18 W	
Depth	23.00 mm	Current type	AC	
Height	410.00 mm	Power factor	0.9	
Finish	Opal	Energy efficiency class	E	
Colour	White	Energy consumption	18 W	
Colour housing	White	Lamp efficacy	127.78	
Body material	Glass	LED		
Lifespan	30000 hours	Filament LED	No	
Switches	15000	LED type	SMD 2835	
Beam angle	270 °	Dimm type	Non-Dim	
Dimmable	No	Number of leds / sticks	96	
Degree of protection	IP20	Colour consistency SDCM	SDCM6	
Net weight	0.119 kg	Dim to warm	No	
Warranty	2 years	Adjustable beam angle	No	
Light		Ordering details		
Kelvin	6500 K	L480103665	Quantity pc(s)	EAN
Colour temp nr	865	Single package	1	8718739071520
Stable lumen	2300 lm	Inner carton	10	18718739071527
Color Rendering Index (CRI)	80	Outer carton	100	28718739071524

