PROFESSIONAL LIGHTING

L642745035

LED GU5.3 MR16 CCT Switch 50x46mm 12V
500Lm 6.5W 3000K/4000K/5000K Ra80
50° AC/DC Helder Dimbaar

Huishoudelijk, Spot MR16 Switch





General	
Eprel registration no	2618208
Socket	GU5.3
Bulb shape	MR16
Width	50.00 mm
Depth	50.00 mm
Height	46.00 mm
Finish	Clear
Colour	Colourless
Colour housing	Silver
Body material	Glass
Lifespan	15000 hours
Switches	7500
Beam angle	50 °
Dimmable	Yes
Degree of protection	IP20
Net weight	0.040 kg
Warranty	2 years

Energy	
Operating voltage	12 V
Volt	10..15 V
Frequency	50..60 Hz
Watt	6.5 W
Current type	AC/DC
Power factor	0.7
Energy efficiency class	G
Energy consumption	7 W
Lamp efficacy	76.92

LED	
Filament LED	No
LED type	SMD
Dimm type	Trailing edge
Number of leds / sticks	16
Colour consistency SDCM	SDCM6
Dim to warm	No
Adjustable beam angle	No

Light	
CRI	80
Kelvin	3000..5000 K
Colour temp nr	830..850
Stable lumen	550 lm
Lumen 90 cone	500 lm
Luminous intensity	600 cd

Ordering details		
L642745035	Quantity pc(s)	EAN
Single package	1	8718739083400
Inner carton	10	18718739083407
Outer carton	100	28718739083404

Remark

Led offers the option for adjusting the colourtemperature. The selectable colour temperatures (CCT's) are 3000K, 4000K and 5000K.

CE | UK CA

Pottenbakkerstraat 35, 4871 EP Etten-Leur, The Netherlands | www.spl-lighting.com | info@spl-lighting.com | Telephone +31 (0)76 - 503 77 17
Fax +31 (0)76 501 78 69 | splprofessionallighting | schiefersignaal