



## LB147225030-1

LED E14 Kogel G45x79mm 100-240V  
270Lm 3W 3000K 830 220° AC/DC Opaal  
Niet-Dimbaar

Huishoudelijk, General VR 100-240V



| General  |              | Energy                  |                |                |
|--|--------------|-------------------------|----------------|----------------|
| Eprel registration no  | 1077471      | Volt                    | 100..240 V     |                |
| Socket   | E14          | Frequency               | 50..60 Hz      |                |
| Bulb shape   | G45          | Watt                    | 3 W            |                |
| Width  | 45.00 mm     | Current type            | AC/DC          |                |
| Depth  | 45.00 mm     | Power factor            | 0.5            |                |
| Height   | 79.00 mm     | Energy efficiency class | F              |                |
| Finish   | Opal         | Energy consumption      | 3 W            |                |
| Colour   | White        | Lamp efficacy           | 90.00          |                |
| Colour housing   | White        | <b>LED</b>              |                |                |
| Body material  | Polycarbonat | Filament LED            | No             |                |
| Lifespan   | 15000 hours  | LED type                | SMD            |                |
| Switches   | 50000        | Dimm type               | Non-Dim        |                |
| Beam angle   | 220 °        | Number of leds / sticks | 4              |                |
| Dimmable   | No           | Colour consistency SDCM | SDCM6          |                |
| Degree of protection   | IP20         | Dim to warm             | No             |                |
| Net weight   | 0.018 kg     | Adjustable beam angle   | No             |                |
| Warranty   | 2 years      | <b>Ordering details</b> |                |                |
| <b>Light</b>   |              | LB147225030-1           | Quantity pc(s) | EAN            |
| Kelvin   | 3000 K       | Single package          | 1              | 8718739066298  |
| Colour temp nr   | 830          | Inner carton            | 10             | 18718739066295 |
| Stable lumen   | 270 lm       | Outer carton            | 100            | 28718739066292 |
| Color Rendering Index (CRI)                                      | 80           |                         |                |                |
| <b>Remark</b>  |              |                         |                |                |
| Data sheet is based on AC, but product can be used on DC as well |              |                         |                |                |

