PROFESSIONAL LIGHTING

LX024061301

LED Ba22d Filament Kaars C35x95mm 230V 380Lm 4W 2500K 925 360° AC Mat Dimbaar

Decoratief, Candle Premium

General	
Eprel registration no	2265059
Socket	Ba22d
Bulb shape	C35
Width	35.00 mm
Depth	35.00 mm
Height	95.00 mm
Finish	Frosted
Colour	Colourless
Body material	Glass
Lifespan	25000 hours
Switches	50000
Beam angle	360 °
Dimmable	Yes
Degree of protection	IP20
Net weight	0.015 kg
Warranty	2 years

Light	
Kelvin	2500 K
Colour temp nr	925
Stable lumen	380 lm
Color Rendering Index (CRI)	93

Energy	
Operating voltage	230 V
Volt	220..240 V
Frequency	50..60 Hz
Watt	4 W
Current type	AC
Power factor	0.9
Energy efficiency class	F
Energy consumption	4 W
Lamp efficacy	95.00

LED	
Filament LED	Yes
LED type	Ceramic
Dimm type	Trailing and leading edge
Number of leds / sticks	4
Stick length	38 mm
Stick mounting	Twisted
Colour consistency SDCM	SDCM6
Dim to warm	No
Adjustable beam angle	No

Ordering details		
LX024061301	Quantity pc(s)	EAN
Single package	1	8718739081079
Inner carton	10	18718739081076
Outer carton	100	28718739081073

CE | UK CA

Pottenbakkerstraat 35, 4871 EP Etten-Leur, The Netherlands | www.spl-lighting.com | info@spl-lighting.com | Telephone +31 (0)76 - 503 77 17
Fax +31 (0)76 501 78 69 | splprofessionallighting | schiefersignaal