PROFESSIONAL LIGHTING

LX229505621

LED Ba22d Filament Tube T30x95mm 230V 470Lm 5W 2700K 927 360° AC Mat Dimbaar

Marine & Industrie, Tubular Filament

General	
Eprel registration no	2462818
Socket	Ba22d
Bulb shape	T30
Width	30.00 mm
Depth	30.00 mm
Height	95.00 mm
Finish	Frosted
Colour	Colourless
Body material	Glass
Lifespan	25000 hours
Switches	50000
Beam angle	360 °
Dimmable	Yes
Degree of protection	IP20
Net weight	0.026 kg
Warranty	2 years

Light	
Kelvin	2700 K
Colour temp nr	927
Stable lumen	470 lm
Color Rendering Index (CRI)	90

Energy	
Operating voltage	230 V
Volt	220..240 V
Frequency	50..60 Hz
Watt	5 W
Current type	AC
Power factor	0.9
Energy efficiency class	F
Energy consumption	5 W
Lamp efficacy	94.00

LED	
Filament LED	Yes
LED type	Ceramic
Dimm type	Trailing and leading edge
Number of leds / sticks	6
Stick length	38 mm
Stick mounting	Straight
Colour consistency SDCM	SDCM6
Dim to warm	No
Adjustable beam angle	No

Ordering details		
LX229505621	Quantity pc(s)	EAN
Single package	1	8718739082830
Inner carton	10	18718739082837
Outer carton	100	28718739082834

CE | UK CA

Pottenbakkerstraat 35, 4871 EP Etten-Leur, The Netherlands | www.spl-lighting.com | info@spl-lighting.com | Telephone +31 (0)76 - 503 77 17
Fax +31 (0)76 501 78 69 | splprofessionallighting | schiefersignaal