

# SLI047313CCT\_PW\_3F

ALLDAY BASIC 20W/30W/40W 3CCT 230V 115DEG IP20 1203x42x37mm BLACK OP 5 YW. 3F



Power	<b>20 / 30 / 40 W</b>	Voltage	<b>230 V</b>
Colour temperature	<b>2700 / 4000 / 6000 K</b>	Colour of light	<b>CCT</b>
Beam angle	<b>115 °</b>	Degree of protection (IP)	<b>IP20</b>

## Technical data

---

Code	SLI047313CCT_PW_3F
Power	20 / 30 / 40 W
Nominal current	175 mA
Voltage	230 V
Energy consumption	20 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power supply included	Yes
Power factor	0.950000
Useful luminous flux*	5000 lm (360°)
Luminous flux	2000 / 3000 / 4000 lm (360°)
Lamp efficacy	125 lm/W
Colour temperature	2700 / 4000 / 6000 K
Colour of light	CCT
Beam angle	115 °
RA	80
Light source included	Yes
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	20 / +40 °
Warranty	5 years
Lifespan	50000 h
(On/Off)	30000
Housing material	aluminum
Degree of protection (IP)	IP20
Colour	Czarny
Dimension (AxBxC)	1203x42x37 mm
For use	Inside
Assembly method	on track 3fazowy
Application	Inside
Made in	PL
Other	Light color change function 2700K / 4000K / 6000K ,

\*applies to the LED source used

## Related documents

---



 Declaration of Conformity