

# WLD+40012\_CCT\_2F

SYSTEM SHIFT CCT- GRID M LINING FITURE 330X23X42MM 17W 40deg BLACK CCT SWITCH 5yw 2F




Power	<b>22 W</b>	Voltage	<b>48 V</b>
Colour temperature	<b>2700 / 3300 / 4000 K</b>	Colour of light	<b>CCT</b>
Beam angle	<b>35 °</b>	Degree of protection (IP)	<b>IP20</b>

## Technical data

Code	WLD+40012_CCT_2F
Power	22 W
Nominal current	450 mA
Voltage	48 V
Energy consumption	22 kWh/1000h
Frequency	DC Hz
Protection class	III
Manufacturer of power supply	tuobo
Power factor	1
Useful luminous flux*	2250 lm (360°)
Luminous flux	1550 lm (360°)
Lamp efficacy	102 lm/W
Luminous intensity	4600 cd
Colour temperature	2700 / 3300 / 4000 K
Colour of light	CCT
Beam angle	35 °
RA	90
Light source included	Yes
Producer of LED diodes	osram
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	20 to +40 °
Warranty	5 years
Lifespan	50000 h
(On/Off)	25000
Housing material	aluminum
Degree of protection (IP)	IP20
Colour	Czarny
Dimension (AxBxC)	404x23x42 mm
For use	Inside
Assembly method	on track 48V
Application	Inside
Made in	PRC
Other	2F ,
Catalogue number	WLD+40012_CCT_2F ,


## Logistics data



\*applies to the LED source used

## Related documents



 Declaration of Conformity

